

Page 1 of 5
UltraMAX® Hair Hold
Sculpting Spray

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.0 SDS Revision Date: 06/26/2023 1. PRODUCT & COMPANY IDENTIFICATION Product Name: UltraMAX® Hair Hold Sculpting Spray (50% VOC) 1.2 Chemical Name: Ethanol Solution Synonyms: NA UltraMAX® Hair Hold Spray Product Use: Hairspray / Animal Care / Grooming 16 Distributor's Name Best Shot Pet Products International, LLC. Distributor's Address: 1.7 180 Commerce Boulevard, Frankfort, Kentucky 40601 mergency Phone +1 (800) 735-5251, 24/7 Poison Control +1 (800) 222-1222 Business Phone / Fax +1 (502) 234-5300, +1 (800) 735-5251 2. HAZARDS IDENTIFICATION Hazard Identification: Prepared in accordance with UN Globally Harmonized standards. Intended to comply with OSHA 29 CFR 1910.1200. Canadian WHMIS and Australian Work Health and Safety standards. DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. Classification: Flam. Liq. 3; Eye Irrit. 2B Label Elements: Hazard Statements (H): H226 – Flammable liquid and vapor. H320 – Causes eye irritation. Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces. No Smoking. P233 – Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P243 - Take precautionary measures against static discharge. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P280 - Wear eye protection/face protection. P305+P351+P338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. P337+P317 - If eye irritation persists: Get medical help. P370+P378 - In case of fire, CO2, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage, or disposal facility (TSDF). Other Warnings: In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. KEEP OUT OF REACH OF CHILDREN. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³)
NOHSC OSHA **ACGIH** NOHSC ES-ES-TLV STEL PEL STEL IDLH CHEMICAL NAME(S) RTECS No. EINECS No TWA STEL PEAK OTHER ETHANOL (SD ALCOHOL 40B) 64-17-5 KQ6300000 200-578-6 45-50 1000 3000 1000 1800 NF 1000 1900 3300 Flam. Liq. 2; H225 WATER (AQUA/EAU) 7732-18-5 231-791-2 10-15 NA NA NF NA PROPRIETARY BLEND NA NA 0.1-10 NA NA NF NF NA NA NA NA 4. FIRST AID MEASURES First Aid: If ingested, do not induce vomiting! Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure Eyes: thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove all contaminated clothing, including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately. Inhalation: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.



Page 2 of 5
UltraMAX® Hair Hold
Sculpting Spray

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.0 SDS Revision Date: 06/26/2023 4. FIRST AID MEASURES - cont'd 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, Eyes: ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Inhalation: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Odor may give some warning of exposure, but odor mav occur. Symptoms of Overexposure Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Acute Health Effects: Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches Chronic Health Effects: The material may accentuate any pre-existing dermatitis condition. Methylparaben contained in very small amounts in this product, may be a mild allergen to some sensitive individuals. Target Organs: Eyes, Skin. Medical Conditions Aggravated by 47 Pre-existing dermatitis, other skin conditions, and disorders of the target HEALTH Exposure: organs (eyes, skin, and respiratory system). FLAMMABILITY 3 PHYSICAL HAZARDS 0 PROTECTIVE EQUIPMENT В EYES SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. 5.2 Extinguishing Methods CO2, Halon (if permitted), Dry Chemical, Foam, water mist. Firefiahtina Procedures: Fight fires according to the surrounding materials. As in any fire, wear an MSHA / NIOSH approved self-contained breathing apparatus (pressurized) and full protective clothing. Keep containers cold long after the fire is out. Use a spray of diffused water to cool the surfaces exposed to the fire and to protect personnel. Fight the fire upstream, Avoid spraying water directly into storage containers due to the danger of overflowing. Prevent runoff from fire control or dilution from entering sewers, drains, potable water supplies or natural waterways. Firefighters must use full response clothing including a NIOSH approved self-contained positive pressure breathing apparatus to protect against potential hazardous combustion or decomposition of products and lack of oxygen. 6. ACCIDENTAL RELEASE MEASURES 6.1 Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.



Page 3 of 5
UltraMAX® Hair Hold
Sculpting Spray

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.0 SDS Revision Date: 06/26/2023 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION OSHA OTHER Exposure Limits: ppm (mg/m³) NOHS STEL ES-TWA STEL IDLH CHEMICAL NAME(S) STE ETHANOL (SD ALCOHOL 40B) 1000 3000 1000 1800 NF 1000 1900 3300 FRAGRANCE NF NA NA NA NA Ventilation & Engineering Controls 8.2 When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. Eye Protection: 8.4 AVOID EYE CONTACT DUE TO SENSITIZATION POTENTIAL. None required under normal conditions of use. Safety glasses with side shields should be used when handling large quantities (e.g., ≥ 1 gallon) of this product. 8.5 Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon), wear rubber or impervious plastic gloves. 8.6 Body Protection: No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Clear homogenous liquid 9.2 Odor Alcohol/sweet pea fragrance 9.3 Odor Threshold: 94 6.90-7.50 9.5 Meltina Point/Freezina Poin NΑ 9.6 Initial Boiling Point/Boiling Range: NA < 24°C (< 75°F) TCC 9.8 Upper/Lower Flammability Limits Vapor Pressure: 9.9 NA 9.10 Vapor Density NΑ 0.894-0.915 9.12 Solubility: 9.13 NA Autoignition Temperature NΑ 9.15 Decomposition Temperature NΑ 9.16 Viscosity: NA Other Information: 9.17 50% VOC 10. STABILITY & REACTIVITY Relatively stable under ambient conditions when stored properly. 10.2 Hazardous Decomposition Products: If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen). 10.3 Hazardous Polymerization: Conditions to Avoid: Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame. ncompatible Substances: 10.5 Strong oxidizers, peroxides, or strong acids.



Page 4 of 5
UltraMAX® Hair Hold
Sculpting Spray

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.0 SDS Revision Date: 06/26/2023 11. TOXICOLOGICAL INFORMATION Routes of Entry: Inhalation: YFS Ingestion: YFS Toxicity Data 11.2 This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components, but is not presented in this document. Acute Toxicity: 11.3 See Section 4.4 11.4 Chronic Toxicity See Section 4.5 Suspected Carcinogen: 11.5 Ethanol: California Proposition 65 ((CA65) ethanol in alcoholic beverages) This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Reproductive Toxicity: 11.6 This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity This product is not reported to cause reproductive effects in humans Irritancy of Product: 11 7 See Section 4.3 Biological Exposure Indices NE Physician Recommendations Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: There are no specific data available for this product. The components of this product will slowly degrade over time into a variety of organic 12.1 compounds. Specific environmental data available for the components of this product are as follows: Ethanol: In water, will volatilize and probably degrade. Effects on Plants & Animals There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product. 13. DISPOSAL CONSIDERATIONS Waste Disposal 13.1 Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Special Considerations Contact the federal, state or provincial environmental authority to determine suitability for recycling and or proper disposal requirements. U.S. EPA Hazardous Waste (Characteristic - Ignitable): D001 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR UN1170, ETHANOL SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1170, ETHANOL SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, 9 (IP IATA (AIR): 4.2 IMDG (OCN): UN1170, ETHANOL SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) 14.3 14.4 TDGR (Canadian GND): UN1170, ETHANOL SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) ADR/RID (EU): UN1170, ETHANOL SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) SCT (MEXICO): 14.6 UN1170, ETHANOL SOLUTION, 3, II, (CANT. LTD, IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1170, ETHANOL SOLUTION, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer 4.8 Package) 15. REGULATORY INFORMATION 15.1 SARA Reporting Requirements This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements. There are no specific Threshold Planning Quantities for the components of this product. 5.2 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 CERCLA Reportable Quantity: Other Federal Requirements: This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA



Page 5 of 5 UltraMAX® Hair Hold **Sculpting Spray**

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.0 SDS Revision Date: 06/26/2023 15. REGULATORY INFORMATION - cont'd 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the HPR and the SDS contains all the information required by the HPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B Flammable, Other Toxic Effects). 15.7 State Regulatory Information: Ethanol is found on the following state criteria list: CA, NJ, FL, MA, MN, PA and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to 15.8 Other Requirements: NA 16. OTHER INFORMATION Other Information: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES SERIOUS EYE IRRITATION. External use only. Use as directed. Discontinue use if irritation develops. Keep away from heat/sparks/open flame/hot surfaces. No Smoking. Keep container tightly closed. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Use only outdoors or in a well-ventilated area. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If irritation persist: Seek medical help. n case of fire, CO, halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep container tightly closed. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & John Paul Mitchell Systems', knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared by Best Shot Pet Products Intl., LLC. 180 Commerce Blvd., Frankfort, Kentucky 40601 USA Tel: +1 (502) 234-5300 Fax: +1 (502) 234-5900



